

TMS-CCUV (clear & UV protection)

TMS-CCUV clear heat shrinkable sleeves are designed for over protection to give increased protection for permanent, long-term environmental exposure. The clear CCUV heat-shrinkable sleeves are formulated to combine a long-term barrier to the effects of ultra-violet, with tough resistance to abrasion and industrial fluids.



Product facts

- 2:1 shrink ratio
- UV-resistance
- Exceptional clarity and stability
- Not printable
- Low profile
- Tough resistance to abrasion and industrial fluids

Temperature

Operating range	-55°C bis +150°C
Min. shrinking temperature	+150°C
Max. stocking temperature	+40°C

Specifications and approvals

- UL VW-1
- SAF-AVIS-DTL-23053/18 class 2

Dimensions in mm

Part Number	Inside diameter		Sleeve length	Cable diameter
	As supplied	After heating		
TMS-CCUV-1-X-65mm	3.20	1.60	65.00	1.8-2.8
TMS-CCUV-2-X-65mm	4.80	2.40	65.00	2.6-3.7
TMS-CCUV-3-X-65mm	6.40	3.20	65.00	3.5-5.1
TMS-CCUV-4-X-65mm	9.50	4.80	65.00	5.0-7.0
TMS-CCUV-5-X-65mm	12.70	6.40	65.00	6.9-10.6
TMS-CCUV-6-X-65mm	19.00	9.50	65.00	10.0-14.0
TMS-CCUV-7-X-65mm	25.40	12.70	65.00	13.3-21.0
TMS-CCUV-8-X-65mm	38.10	19.00	65.00	21.0-33.8

Packing unit: 250 pieces

Colours

Colour	clear
Ordering code	-X

Please contact us for further information, prices and lead-time.