

## Heat shrink sleeves, HT-CT, high temperature continuous tube

HT-CT heat shrink tube is manufactured using a special radiation cross-linked material to provide high temperature performance and low out-gassing, suitable for many military and aerospace applications. Cut in length the printable heat shrink tube HT-CT can be used as heat shrink sleeves for identification of cables and wires.



### Product facts of identification sleeves HT-CT

- High temperature
- Excellent chemical resistance
- Resistant to key aerospace, military, rail and industrial fluids
- Flame retarded, self-extinguishing, UL VW-1 rated
- Printable with thermal transfer printers
- Open profile for easier use

### Temperature

Operating range	-55°C to +225°C
Recommended ribbon	TMS-RJS-RIBBON-9HT-MED

### Specifications and approvals of identification sleeves HT-CT

- EN45545-2, R24
- NFPA 130
- UL VW-1

### Dimensions in mm

Part Number	Inside diameter		Spool In meter	Colour
	As supplied	After heating		
HT-CT-50M-3/32-OUT-4	2.4	0.79	50	Yellow
HT-CT-50M-1/8-OUT-4	3.2	1.6	50	Yellow
HT-CT-50M-3/16-OUT-4	4.8	2.4	50	Yellow
HT-CT-50M-1/4-OUT-4	6.4	3.2	50	Yellow
HT-CT-50M-3/8-OUT-4	9.5	4.8	50	Yellow
HT-CT-50M-1/2-OUT-4	12.7	6.4	50	Yellow
HT-CT-50M-3/4-OUT-4	19.1	9.5	50	Yellow
HT-CT-50M-3/32-OUT-9	2.4	0.79	50	White
HT-CT-50M-1/8-OUT-9	3.2	1.6	50	White
HT-CT-50M-3/16-OUT-9	4.8	2.4	50	White
HT-CT-50M-1/4-OUT-9	6.4	3.2	50	White
HT-CT-50M-3/8-OUT-9	9.5	4.8	50	White
HT-CT-50M-1/2-OUT-9	12.7	6.4	50	White
HT-CT-50M-3/4-OUT-9	19.1	9.5	50	White