

Heat shrink sleeves, HX-SCE, halogen free

HX-SCE identification heat shrink sleeves are used to identify wires and cables where low fire hazard properties are critical. The zero halogen material coupled with low smoke and low toxic fume emissions make this product ideal for use in enclosed spaces such as mass transit, marine and industrial installations.



Product facts of identification sleeves HX-SCE

- EN-45545-2 approved
- Thermal transfer printable
- Zero halogen
- Low toxic fumes
- Low smoke
- Self extinguishing, non-flame propagating
- Excellent resistance to burning – Oxygen Index 39%
- Resistant to key industrial and rail fluids

Temperature

Operating range	-55°C to +105°C
Recommended ribbon	1966-Ribbon





Specifications and approvals of identification sleeves Hx-SCE

- EN45545-2, R22, R23, R24, HL3
- BS 6853 vehicle CAT 1A
- NFPA130
- NF F 16-101 Classification A1
- London Underground 1-085

Dimensions in mm

Part Number	Inside diameter		Packing unit	Colour
	As supplied	After heating		
HX-SCE-5K-2.4-50-4	2.40	1.20	5000 Pieces	Yellow
HX-SCE-5K-3.2-50-4	3.20	1.60	5000 Pieces	Yellow
HX-SCE-2.5K-4.8-50-4	4.80	2.40	2500 Pieces	Yellow
HX-SCE-2.5K-6.4-50-4	6.40	3.20	2500 Pieces	Yellow
HX-SCE-1K-9.5-50-4	9.50	4.80	1000 Pieces	Yellow
HX-SCE-1K-12.7-50-4	12.70	6.40	1000 Pieces	Yellow
HX-SCE-1K-19.0-50-4	19.00	9.60	1000 Pieces	Yellow
HX-SCE-1K-25.4-50-4	25.40	12.70	1000 Pieces	Yellow
HX-SCE-38.1-50-4	38.10	19.10	250 Pieces	Yellow
HX-SCE-5K-2.4-50-9	2.40	1.20	5000 Pieces	White
HX-SCE-5K-3.2-50-9	3.20	1.60	5000 Pieces	White
HX-SCE-2.5K-4.8-50-9	4.80	2.40	2500 Pieces	White
HX-SCE-2.5K-6.4-50-9	6.40	3.20	2500 Pieces	White
HX-SCE-1K-9.5-50-9	9.50	4.80	1000 Pieces	White
HX-SCE-1K-12.7-50-9	12.70	6.40	1000 Pieces	White
HX-SCE-1K-19.0-50-9	19.00	9.60	1000 Pieces	White
HX-SCE-1K-25.4-50-9	25.40	12.70	1000 Pieces	White
HX-SCE-38.1-50-9	38.10	19.10	250 Pieces	White

Available options: perforation (to produce multiple markers per sleeve)

Standard	1 perforation (-S1)	2 perforations (-S2)	3 perforations (-S3)
			

Standard colours (non-standard available on request: blue, green, orange, red)

Colour	Yellow	White
Ordering code	-4	-9

