

Heat shrink sleeves, TMS-CT, military grade continuous tube

TMS-CT heat shrink tube is manufactured using a special radiation cross-linked material to provide mechanical protection and easy identification to wires and cables for military applications. This light weight heat shrink tube is often used for military, aerospace, industrial and energy applications. Cut in length the printable heat shrink tube TMS-CT can be used as heat shrink sleeves for identification of cables and wires.



Product facts of identification sleeves TMS-CT

- Self-extinguishing, non-flame propagating
- Resistant to key military and aerospace fluids
- Can be laser marked
- Military grade performance
- Printable with thermal transfer printers
- Open profile for easier use

Temperature

Operating range	-55°C to +135°C
Recommended ribbon	TMS-RJS-RIBBON-4RPSCE

Specifications and approvals of identification sleeves TMS-CT

- EN45545-2, R24
- NFPA 130
- SAE-AMS-23053/5 class 1
- CSA 31929
- UL E35586

Dimensions in mm

Part Number	Inside diameter		Spool	Colour
	As supplied	After heating		
TMS-CT-50-3/32-OUT-4	2.4	0.8	50	Yellow
TMS-CT-50-1/8-OUT-4	3.2	1.1	50	Yellow
TMS-CT-50-3/16-OUT-4	4.8	1.6	50	Yellow
TMS-CT-50-1/4-OUT-4	6.4	2.1	50	Yellow
TMS-CT-50-3/8-OUT-4	9.5	3.2	50	Yellow
TMS-CT-50-1/2-OUT-4	12.7	4.2	50	Yellow
TMS-CT-50-3/4-OUT-4	19.1	6.4	50	Yellow
TMS-CT-50-3/32-OUT-9	2.4	0.8	50	White
TMS-CT-50-1/8-OUT-9	3.2	1.1	50	White
TMS-CT-50-3/16-OUT-9	4.8	1.6	50	White
TMS-CT-50-1/4-OUT-9	6.4	2.1	50	White
TMS-CT-50-3/8-OUT-9	9.5	3.2	50	White
TMS-CT-50-1/2-OUT-9	12.7	4.2	50	White
TMS-CT-50-3/4-OUT-9	19.1	6.4	50	White