

Heat shrink sleeves, ZHD-CT, military grade continuous tube

ZHD-CT heat shrink tube is manufactured using a special radiation cross-linked material to provide zero halogen properties with the added benefit of diesel resistance, specifically designed to bridge the gap for installations where the highest performance is demanded from an identification sleeve, without compromising on safety or capability. This light weight heat shrink tube is often used for military, aerospace and rail applications. Cut in length the printable heat shrink tube ZHD-CT can be used as heat shrink sleeves for identification of cables and wires.



Product facts of identification sleeves ZHD-CT

- Zero Halogen
- Diesel resistant
- Self-extinguishing, non-flame propagating
- Resistant to key rail and industrial fluids
- Printable with thermal transfer printers
- Open profile for easier use

Temperature

Operating range -55°C to +125°C

Specifications and approvals of identification sleeves ZHD-CT

- EN45545-2, R22, R23
- BS 6853, 1a
- EN 50343
- NFPA 130
- MIL-STD-202J, method 215K
- SAE AS 5942

Dimensions in mm

Part Number	Inside diameter		Spool In meter	Colour
	As supplied	After heating		
ZHD-CT-50M-2.4-OUT-4	2.4	1.2		Yellow
ZHD-CT-50M-3.2-OUT-4	3.2	1.6		Yellow
ZHD-CT-50M-4.8-OUT-4	4.8	2.4		Yellow
ZHD-CT-50M-6.4-OUT-4	6.4	3.2		Yellow
ZHD-CT-50M-9.5-OUT-4	9.5	4.8		Yellow
ZHD-CT-50M-12.7-OUT-4	12.7	6.4		Yellow
ZHD-CT-50M-19.0-OUT-4	19.1	9.5		Yellow
ZHD-CT-40M-25.4-OUT-4	25.4	12.7		Yellow
ZHD-CT-40M-38.1-OUT-4	38.1	19.1		Yellow
ZHD-CT-50M-2.4-OUT-9	2.4	1.2		White
ZHD-CT-50M-3.2-OUT-9	3.2	1.6		White
ZHD-CT-50M-4.8-OUT-9	4.8	2.4		White
ZHD-CT-50M-6.4-OUT-9	6.4	3.2		White
ZHD-CT-50M-9.5-OUT-9	9.5	4.8		White
ZHD-CT-50M-12.7-OUT-9	12.7	6.4		White
ZHD-CT-50M-19.0-OUT-9	19.1	9.5		White
ZHD-CT-40M-25.4-OUT-9	25.4	12.7		White
ZHD-CT-40M-38.1-OUT-9	38.1	19.1		White