

## Heat shrink tube with adhesive, HTAT, high temperature

HTAT has an internal adhesive coating, that when heated, melts and flows to form a positive environmental barrier to prevent moisture penetration. Used to seal backend connectors, wire splices, breakouts, cable jackets and electrical components.



### Product facts of heat shrink tube HTAT

- 4:1 shrink ratio
- Environmentally seals and protects
- Excellent abrasion and mechanical protection
- Bonds to plastics, rubbers and metals, including PVC and polyethylene

### Temperature

Operating range	-55°C to +125°C
Min. shrinking temperature	+80°C
Min. full recovery temperature	+80°C

### Specifications and approvals of heat shrink tube HTAT

- Raychem RW 2052

### Sizes in mm

Part Number	Inside diameter		Wall thickness	Pieces of 1.2 Meter
	As supplied	After heating	After heating +/- 5%	in Meter
HTAT-4/1-0-Stk	4.00	1.00	1.00	30
HTAT-8/2-0-Stk	8.00	2.00	1.00	30
HTAT-12/3-0-Stk	12.00	3.00	1.40	30
HTAT-16/4-0-Stk	16.00	4.00	1.80	30
HTAT-24/6-0-Stk	24.00	6.00	2.25	30
HTAT-32/8-0-Stk	32.00	8.00	2.55	12
HTAT-48/13-0-Stk	48.00	13.00	2.55	6

### Standard Colour

Colour	Black
Ordering code	0