

Heat shrink tube, DCPT, dual colour, yellow/green, spoolbox

The heat shrinking tube DCPT is used to identify “ground” on wires and in cables, and to jacket and insulate light-duty harnesses. Easily marked by conventional techniques for additional identification of wires and cables. This heat shrink tube can be easily installed. This version is packed in small spools (mini-spools, spoolbox).



Product Facts of heat shrink tube DCPT Spoolboxes

- 2:1 and 3:1 shrink ratio
- Dual colours (yellow/green)
- Flame-retardant
- Flexible
- Outstanding physical and electrical performance
- Excellent chemical and solvent-resistance properties

Temperature

Operating range	-55°C to +135°C
Min. shrinking temperature	+95°C
Min. full recovery temperature	+120°C

Specifications and Approvals of heat shrink tube DCPT Spoolboxes

- UL File E35586
- CSA LR31929
- Def. Stan. 59-97 Issue 3 Type 2B
- VG 95343 Part 5 Type A



Dimensions in mm

Part Number	Inside Diameter		Wall Thickness After Heating +/- 5%	Reel in Meter
	As Supplied	After Heating		
DCPT-R-3/1.5-45	3.00	1.50	0.50	5
DCPT-R-6/3-45	6.00	3.00	0.60	3.5
DCPT-R-8/4-45	8.00	4.00	0.65	3
DCPT-R-10/5-45	10.00	5.00	0.65	2.5
DCPT-R-19/9-45	19.00	9.00	0.75	2
DCPT-R-26/13-45	26.00	13.00	0.90	1.5

Standard Colour

Colour	Yellow / Green
Ordering Code	45