

## Heat shrink tube, LSTT, low shrink temperature, in small boxes

LSTT is a highly flexible, low-shrink-temperature, heat-shrinkable tubing. Its low shrink temperature offers exceptionally fast recovery for maximum efficiency in high-volume commercial applications and makes it suitable for use on or near delicate, temperature-sensitive materials, such as PVC jacketed wire and cable. Although not flame-retardant, LSTT meets the automotive flame propagation standard MVSS 302. This version is packed in small spools (mini-spools, spoolbox).



### Product Facts of heat shrink tube LSTT Spoolbox

- 2:1 shrink ratio
- Rapid recovery at low temperatures
- Can be used with temperature-sensitive materials
- Flexible
- Excellent physical and electrical performance

### Temperature

Operating range	-40°C to +125°C
Min. shrinking temperature	+65°C
Min. full recovery temperature	+110°C

### Specifications and Approvals of heat shrink tube LSTT Spoolbox

- RW 2051



### Dimensions in mm

Part Number	Inside Diameter		Wall Thickness	Content per Box in Meter
	As Supplied	After Heating	After Heating +/- 5%	
LSTT-R-2.4-0	2.40	1.20	0.55	10
LSTT-R-3.2-0	3.20	1.60	0.55	10
LSTT-R-4.8-0	4.80	2.40	0.55	9
LSTT-R-6.4-0	6.40	3.20	0.65	8
LSTT-R-9.5-0	9.50	4.80	0.65	6
LSTT-R-12.7-0	12.70	6.40	0.65	6
LSTT-R-19.0-0	19.00	9.50	0.80	5
LSTT-R-25.4-0	25.40	12.70	0.95	3

### Standard Colour

Colour	Black
Ordering Code	0