


Heat shrink tube, ZH-100, halogen free

ZH-100 is a flexible, thin-wall, heat-shrinkable tubing designed for low-fire-hazard applications. ZH-100 contains no added halogens and exhibits excellent fire safety characteristics combined with low evolution of acid gases, while retaining good mechanical and fluid resistance properties.



Product Facts of heat shrink tube ZH-100

- 2:1 shrink ratio
- Low smoke emissions
- No added halogens
- Flexible, flame-retardant
- Low evolution of acid gases

Temperature

Operating range	-30°C to +105°C
Min. shrinking temperature	+80°C
Min. full recovery temperature	+120°C

Specifications and Approvals of heat shrink tube ZH-100

- BR 1326A



Dimensions in mm

Part Number	Inside Diameter		Wall Thickness	Reels
	As Supplied	After Heating	After Heating +/- 5%	in Meter
ZH-100-1/8-0-SP	3.20	1.60	0.50	150
ZH-100-3/16-0-SP	4.80	2.40	0.50	150
ZH-100-1/4-0-SP	6.40	3.20	0.65	75
ZH-100-3/8-0-SP	9.50	4.80	0.65	75
ZH-100-1/2-0-SP	12.70	6.40	0.65	75
ZH-100-3/4-0-SP	19.00	9.50	0.75	75
ZH-100-1-0-SP	25.40	12.70	0.90	30
ZH-100-1-1/2-0-SP	38.00	19.00	1.00	30
ZH-100-2-0-SP	51.00	25.40	1.15	30

Standard Colour

Colour	Black
Ordering Code	0