

## Clear Polyester Labels CP

CP is a thermal transfer printable clear polyester label with a permanent acrylic adhesive. CP can be used as an over laminate to further protect printed labels from chemicals, solvents, abrasion, heat and moisture. Designed for rating plates, nameplates, equipment labels, serial number plates and general labelling applications that require a high durability transparent label.



### Product Facts

- Temperature Range: -40°C to +150°C
- Thermal transfer printable
- For general labelling applications
- Chemical resistant
- Can be used as an over-laminate
- Excellent adhesion to many materials

### Hardware and Software

- Printer: TE3112 / TE3124
- Ribbon: 1330-0607-10
- Software: Wintotal or Printeasy

### Specification

- MIL-STD-202 Method 215
- MIL-AA-59485 test method MIL-P-38477A

Part Number	Alias	Reel	Width in mm	Height in mm
CP-165051-25-X	A47065-000	25000	16.5	5.1
CP-165102-10-X	F27532-000	10000	16.5	10.2
CP-191064-10-X	E91503-000	10000	19.1	6.4
CP-229064-10-X	E74120-000	10000	22.9	6.4
CP-254097-10-X	C43784-000	10000	25.4	9.7
CP-254127-10-X	E37476-000	10000	25.4	12.7
CP-254254-10-X	D71439-0000	10000	25.4	25.4
CP-381064-10-X	D17392-000	10000	38.1	6.4
CP-381127-5-X	A47961-000	5000	38.1	12.7
CP-381191-5-X	C53708-000	5000	38.1	19.1
CP-406254-1.5-X	D97399-000	1500	40.6	25.4
CP-508127-5-X	A21105-000	5000	50.8	12.7
CP-508254-5-X	A27907-000	5000	50.8	25.4
CP-508318-2.5-X	F41633-000	2500	50.8	31.8
CP-699254-5-X	F81616-000	5000	69.9	25.4
CP-762381-2.5-X	A67962-000	2500	76.2	38.1
CP-101508-2.5-X	E08328-000	2500	101.6	50.8
CP-101635-2.5-X	F97579-000	2500	101.6	63.5