
Raytronics AG

Wärmeschrumpftechnik

Panel Label PL

A cost effective, commercially attractive replacement for engraved labels using a high performance, thermal transfer label with a foam backed adhesive. Our Panel Labels are suitable for on-demand printing. Ideal for use with high definition graphics and barcodes. These are suitable for indoor and outdoor use and conform to the durability specifications of the UL969 Marking and Labelling standard. It is available in white or silver, with other colours possible on request. Compatible with all TE thermal transfer printers and data input using the TE WinTotal software.



Product Facts

- Thermal transfer printable
- Temperature Range: -40°C to +80°C
- Saving of product and install costs compared to engraved labels
- Clean creation and installation process
- Suitable for on-demand printing
- Able to create and print high definition graphics and barcodes
- Indoor and outdoor use
- Conforms to UL969 marking and labelling specification

Specification

- UL recognized PGJI2 and PGJI8 – File MH17292:

PL-9 for Gloss White PL-8A for Satin Metalized

This datasheet is issued without guarantee according to the correctness of the containing information, product and service descriptions. The data has been carefully checked, Raytronics AG is not liable for any loss or damage resulting from errors or omission in hereby contained information.

Raytronics AG

Wärmeschrumpftechnik

Sizes in mm

Part Number	Label Height	Laber Width	Web Width	Labels	Labels	Colour
	mm	mm	mm	Per row	Per reel	
PL-027008-2.5-8A	8.0	27.0	37.0	1	2500	Silber
PL-027008-2.5-9	8.0	27.0	37.0	1	2500	Weiss
PL-027013-1.5-8A	13.0	27.0	37.0	1	1500	Silber
PL-027013-1.5-9	13.0	27.0	37.0	1	1500	Weiss
PL-027018-1.25-8A	18.0	27.0	37.0	1	1250	Silber
PL-027018-1.25-9	18.0	27.0	37.0	1	1250	Weiss
PL-027027-1-8A	27.0	27.0	37.0	1	1000	Silber
PL-027027-1-9	27.0	27.0	37.0	1	1000	Weiss
PL-035018-1.25-8A	18.0	35.0	45.0	1	1250	Silber
PL-035018-1.25-9	18.0	35.0	45.0	1	1250	Weiss
PL-036028.5-0.75-8A	28.5	36.0	46.0	1	750	Silber
PL-036028.5-0.75-9	28.5	36.0	46.0	1	750	Weiss
PL-045015-1.5-8A	15.0	45.0	55.0	1	1500	Silber
PL-045015-1.5-9	15.0	45.0	55.0	1	1500	Weiss
PL-050025-1-8A	25.0	50.0	60.0	1	1000	Silber
PL-050025-1-9	25.0	50.0	60.0	1	1000	Weiss
PL-060030-0.75-8A	30.0	60.0	70.0	1	750	Silber
PL-060030-0.75-9	30.0	60.0	70.0	1	750	Weiss
PL-090045-0.5-8A	45.0	90.0	100.0	1	500	Silber
PL-090045-0.5-9	45.0	90.0	100.0	1	500	Weiss
PL-100050-0.5-8A	50.0	100.0	106.0	1	500	Silber
PL-100050-0.5-9	50.0	100.0	106.0	1	500	Weiss