

End caps 101A011 to 101A094 (moulded parts, thin wall)

These end caps provides water-proofing and environmental protection for underwater, underground and outdoor applications. These moulded parts are resistant to moisture, fungus and weathering. The heat shrink boots 101A011 to 101A094 are used for protecting cables, wires and pipes or capping unused outlets in transitions. When used with adhesive these end caps provides an environmental seal.

As supplied



After heating



Dimensions in mm

Part number	Inside diameter (coating reduces \varnothing max. 1.5mm)		Total length	Wall thickness +/- 20%
	As supplied	After shrinking		
101A011	5.10	2.00	22.90	1.02
101A021	7.40	3.30	25.40	1.27
101A031	10.20	4.80	30.50	1.52
101A041	15.20	6.40	40.60	1.78
101A052	20.60	9.40	61.00	2.03
101A062	25.40	11.40	68.80	2.29
101A073	39.40	18.00	91.40	2.54
101A083	50.80	22.90	101.60	2.79
101A094	83.80	38.10	114.30	3.05

Material (not all combinations available)

Ordering Code	Material	Operating temperature range
-3	Polyolefin, semi-rigid	-55°C to +135°C
-4	Polyolefin, flexible	-55°C to +135°C
-12	Fluoroelastomer, flexible	-55°C to +200°C
-25	Elastomer, fluid resistant	-75°C to +150°C
-100	Polyolefin, halogen free	-30°C to +105°C

Coating, Adhesive

Ordering code	Material	Operating temperature range
/42	Polyamide, hot-melt	-20°C to +60°C
/86	High performance, hot-melt	-55°C to +120°C
/225	Epoxy/Polyamide	-75°C to +150°C

Colour

Ordering Code	Colour
-0	Black