
Raytronics AG

Wärmeschrumpftechnik

CWT-3 to CWT-13, solder sleeves moisture proof, short version



Product	Product Dimensions			Prepared Cable Dimensions						
Name	ØA	ØB	L	ØD	ØE	ØF	ØG	н	J	
	min	min	max	max	min	min	max			
CWT-3	2.50	3.00	24.5	3.00	1.50	1.00	2.50	6.0 0.5	7.0 0.5	
	[0.098]	[0.118]	[0.965]	[0.118]	[0.060]	[0.040]	[0.098]	[0.236±0.020]	[0.726±0.020]	
CWT-5	4.30	4.80	29.3	4.80	2.00	1.50	4.30	8.0 0.5	9.0 0.5	
	[0.170]	[0.189]	[1.154]	[0.189]	[0.079]	[0.059]	[0.170]	[0.315±0.020]	[0.354±0.020]	
CWT-6	6.00	6.70	32.00	6.70	3.30	2.80	6.00	9.0 0.5	10.0 0.5	
	[0.236]	[0.264]	[1.260]	[0.264]	[0.130]	[0.110]	[0.236]	[0.354±0.020]	[0.394±0.020]	
CWT-7	6.80	7.30	32.50	7.30	3.30	2.80	6.80	10.0 1.0	11.0 1.0	
	[0.268]	[0.287]	[1.280]	[0.287]	[0.130]	[0.110]	[0.268]	[0.394±0.040]	[0.433±0.040]	
CWT-9	8.70	9.20	35.50	9.20	4.50	4.00	8.70	11.0 1.0	12.0 1.0	
	[0.343]	[0.362]	[1.398]	[0.362]	[0.177]	[0.157]	[0.343]	[0.433±0.040]	[0.472±0.040]	
CWT-11	10.80	11.50	35.50	11.50	4.50	4.00	10.80	12.0 1.0	13.0 1.0	
	[0.425]	[0.453]	[1.398]	[0.453]	[0.177]	[0.157]	[0.425]	[0.472±0.040]	[0.512±0.040]	
CWT-13	13.00	15.10	45.50	15.10	7.00	6.50	13.00	16.0 1.0	17.0 1.0	
011-13	[0.512]	[0.594]	[1.791]	[0.594]	[0.276]	[0.256]	[0.512]	[0.630±0.040]	[0.670±0.040]	

MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, radiation cross-linked modified polyolefin. Color: transparent clear.


2. SOLDER PREFORM WITH FLUX:

SOLDER: TYPE Cd18 per ANSI/J-STD-006.

FLUX: TYPE ROM1 per ANSI/J-STD-004.

MELTABLE SEALING RING: Thermally stabilized thermoplastic. Color: blue (size 3, 5, 6, 7, 9, 11); natural (size 13)
MELTABLE SEALING RING: Thermally stabilized thermoplastic. Color: blue (size 3, 5, 7, 11); gray (size 6); natural (size 9, 13)

For best results, prepare the cable as shown:



TE Connectivity, TE connectivity (logo), Raychem, and SolderSleeve are trademarks

			R	aychem	TITLE: Soldersleeve Shield Terminator					
Unless otherwise specified dimensions are in millimeters. [Inches dimensions are shown in brackets] TOLERANCES: ANGLES: N/A TE Connectivity reserves the right to amend					DOCUMENT NO.: CWT -XX					
0.00 N/A 0.0 N/A 0 N/A		this drawing at any time. Users she evaluate the suitability of the produ		ng at any time. Users should he suitability of the product for their	Revision: 5	Issue Date: April 2020				
PREPARED BY: mforonda		CAGE CODE : 06090		DATE: 15-Apr-11	ECO: ECO-20-004959	SCALE:	SIZE: A	SHEET: 1 of 1		