

## Ringkabelschuhe 0.1 – 6 mm<sup>2</sup>

**Material:** E-Kupfer, elektrolytisch verzinkt, hartgelöteter Hals

PC-Isolierung mit EasyEntry, PC und PA Isolierung sind halogenfrei



|        | mm <sup>2</sup> | Kat Nr | Schraube | mm W | d   | t    | L <sub>1</sub> | L    | s | System Werkzeug | VPE | Isol-mat. |
|--------|-----------------|--------|----------|------|-----|------|----------------|------|---|-----------------|-----|-----------|
| Yellow | 0,1-0,5         | A0522R | M2       | 5,4  | 2,0 | 0,5  | 14,0           | 16,0 | 6 | DSA0115         | 100 | PA*       |
|        |                 | A0532R | M3       | 5,0  | 2,0 | 0,5  | 14,0           | 16,0 | 6 | DSA0115         | 100 | PA*       |
|        |                 | A0543R | M4       | 7,0  | 2,0 | 0,5  | 16,0           | 19,0 | 6 | DSA0115         | 100 | PA*       |
|        |                 | A0553R | M5       | 8,0  | 2,0 | 0,5  | 15,0           | 19,0 | 6 | DSA0115         | 100 | PA*       |
| Green  | 0,25-0,75       | A0832R | M3       | 5,5  | 3,2 | 0,5  | 15,0           | 18,0 | 7 | DSA0115         | 100 | PC        |
|        |                 | A0837R | M3,5     | 6,2  | 3,2 | 0,5  | 17,5           | 21   | 7 | DSA0115         | 100 | PC        |
|        |                 | A0843R | M4       | 7,5  | 3,2 | 0,5  | 17,5           | 21   | 7 | DSA0115         | 100 | PC        |
|        |                 | A0853R | M5       | 9    | 3,2 | 0,5  | 17,5           | 22   | 7 | DSA0115         | 100 | PC        |
| Red    | 0,5-1,5         | A1532R | M3       | 5,5  | 4,0 | 0,7  | 16,0           | 19,0 | 7 | GSA0760         | 100 | PC        |
|        |                 | A1537R | M3,5     | 6,0  | 4,0 | 0,7  | 16             | 19   | 7 | GSA0760         | 100 | PC        |
|        |                 | A1543R | M4       | 7,5  | 4,0 | 0,7  | 17             | 20,5 | 7 | GSA0760         | 100 | PC        |
|        |                 | A1553R | M5       | 9,0  | 4,0 | 0,7  | 18             | 22,5 | 7 | GSA0760         | 100 | PC        |
|        |                 | A1565R | M6       | 11,0 | 4,0 | 0,7  | 21             | 26,5 | 7 | GSA0760         | 100 | PC        |
|        |                 | A1585R | M8       | 14,0 | 4,0 | 0,7  | 20             | 27,5 | 7 | GSA0760         | 100 | PC        |
|        |                 | A1510R | M10      | 16,5 | 4,0 | 0,7  | 22             | 30,5 | 7 | GSA0760         | 100 | PC        |
| Blue   | 1,5-2,5         | A2532R | M3       | 5,5  | 4,5 | 0,8  | 16             | 19   | 8 | GSA0760         | 100 | PC        |
|        |                 | A2537R | M3,5     | 6    | 4,5 | 0,8  | 16             | 19   | 8 | GSA0760         | 100 | PC        |
|        |                 | A2543R | M4       | 7    | 4,5 | 0,8  | 17,5           | 21   | 8 | GSA0760         | 100 | PC        |
|        |                 | A2553R | M5       | 9,0  | 4,5 | 0,8  | 18             | 23   | 8 | GSA0760         | 100 | PC        |
|        |                 | A2565R | M6       | 11,0 | 4,5 | 0,8  | 20,6           | 26,1 | 8 | GSA0760         | 100 | PC        |
|        |                 | A2585R | M8       | 14,0 | 4,5 | 0,8  | 20             | 27,5 | 8 | GSA0760         | 100 | PC        |
|        |                 | A2510R | M10      | 16,5 | 4,5 | 0,75 | 22             | 30,5 | 8 | GSA0760         | 100 | PC        |
|        |                 | A2513R | M12      | 19,0 | 4,5 | 0,75 | 25             | 34   | 8 | GSA0760         | 100 | PA        |
| Yellow | 4-6             | A4643R | M4       | 7,8  | 6,4 | 1,0  | 20,5           | 24,5 | 9 | GSA0760         | 100 | PC        |
|        |                 | A4653R | M5       | 9,0  | 6,4 | 1,0  | 20,5           | 25   | 9 | GSA0760         | 100 | PC        |
|        |                 | A4665R | M6       | 11,0 | 6,4 | 1,0  | 23             | 28,5 | 9 | GSA0760         | 100 | PC        |
|        |                 | A4685R | M8       | 14,0 | 6,4 | 1,0  | 23,8           | 30,8 | 9 | GSA0760         | 100 | PC        |
|        |                 | A4610R | M10      | 17,0 | 6,4 | 1,0  | 25,5           | 34   | 9 | GSA0760         | 50  | PC        |
|        |                 | A4613R | M12      | 19,2 | 6,8 | 1,0  | 31             | 40   | 9 | GSA0760         | 50  | PVC*      |

t = Materialstärke s = Abisolierlänge \* nicht EasyEntry