MicroFit (kleiner Durchmesser)

Die MicroFit-Schrumpfschläuche sind ideal geeignet für elektrische Isolierung, mechanischen Schutz und Zugentlastung in kompakten medizinischen Geräten. Die MicroFit Schrumpfschläuche überzeugend durch genaue Toleranzen bei sehr kleinen Durchmessern.

Auf Wunsch werden diese Schläuche doppelt verpackt und mit CoC geliefert.

Eigenschaften und Nutzen

- Sehr kleine Durchmesser
- Grosses Schrumpfverhältnis
- Dünnwandig
- Doppelt verpackt

Spezifikationen und Zulassungen

- USPClass VI

Abmessungen in mm

Artikelnummer	Innendurchmesser		Wandstärke		Farbe
	Bei Lieferung	Nach Schrumpfung	Bei Lieferung	Nach Schrumpfung	
MFT-MT1000-No.14-X-SP	0.356 (0.014)	0.203 (0.008)	0.076 (0.003)	0.152 (0.006)	Transparent
MFT-MT1000-No.2-X-SP	0.610 (0.024)	0.305 (0.012)	0.064 (0.0025)	0.152 (0.006)	Transparent
MFT-MT1000-No.33-X-SP	1.143 (0.045)	0.432 (0.017)	0.064 (0.0025)	0.118 (0.007)	Transparent
MFT-MT1000-No.65-X-SP	0.635 (0.025)	0.254 (0.010)	0.127 (0.005)	0.330 (0.013)	Transparent
MFT-MT2000-No.14-X-SP	0.356 (0.014)	0.203 (0.008)	0.076 (0.003)	0.152 (0.006)	Transparent
MFT-MT2000-No.2-X-SP	0.610 (0.024)	0.305 (0.012)	0.064 (0.0025)	0.152 (0.006)	Transparent
MFT-MT2000-No.33-X-SP	1.143 (0.045)	0.432 (0.017)	0.064 (0.0025)	0.118 (0.007)	Transparent
MFT-MT2000-No.65-X-SP	0.635 (0.025)	0.254 (0.010)	0.127 (0.005)	0.330 (0.013)	Transparent

(Andere Farben und Grössen auf Anfrage erhältlich)

	MT1000	MT2000
Temperaturbereich	-55°C bis +150°C	-40°C bis +105°C
min. Schrumpftemperatur	+175°C	+140°C
Material	halbsteifes Polyvinyliden Fluorid	medical grade Polyolefin

This datasheet is issued without guarantee according to the correctness of the containing information, product and service descriptions. The data has been carefully checked, Raytronics AG is not liable for any loss or damage resulting from errors or omission in hereby contained information.