

## Battery powered crimp tool



PV130P, PV130S - Elpress Mini.

### Technical data:

- NiMH battery power (9.6 V and 2.0 Ah), recharge time approx. 40 minutes
- advanced ergonomoy for excellent access in confined areas
- tool for service and installation work
- fast crimping 2-4 seconds
- approx. 150 crimps per charge
- crimp ranges see table below
- supplied in a plastic case with battery charger and one battery

### PV130P – Elpress Mini

Battery powered tool for parallel action crimping of pre-insulated terminals up to 6 mm<sup>2</sup>, un-insulated terminals up to 10 mm<sup>2</sup> and end terminals up to 50 mm<sup>2</sup>.

#### Included:

- Battery: PVBP1-MH
- Charger: PVBC2

| Area                                 | Cat. no.              | Weight | Length |
|--------------------------------------|-----------------------|--------|--------|
| 0.5-6/0.25-10/0.5-50 mm <sup>2</sup> | PV130P - Elpress Mini | 1.3 kg | 360 mm |



PV130P, box and charger.

### PV130S – Elpress Mini

Battery powered tool for scissor crimping movement of pre-insulated terminals up to 6 mm<sup>2</sup>, un-insulated terminals up to 10 mm<sup>2</sup> and end terminals up to 50 mm<sup>2</sup>.

#### Included:

- Battery: PVBP1-MH
- Charger: PVBC2

| Area                                 | Cat. no.              | Weight | Length |
|--------------------------------------|-----------------------|--------|--------|
| 0.5-6/0.25-10/0.5-50 mm <sup>2</sup> | PV130S - Elpress Mini | 1.5 kg | 360 mm |



EB0560      WB4099      KB0325



EB3550      EB1025      EB4010



RB0560

## Die Table

|                                                     | PV130P | PV130S |
|-----------------------------------------------------|--------|--------|
| Application                                         | Die    | Die    |
| Pre-insulated 0.5-6 mm <sup>2</sup>                 | SA0760 | SA0760 |
| Un-insulated, indent crimp 0.25-2.5 mm <sup>2</sup> | KB0325 | KB0325 |
| Un-insulated, W crimp 4-10 mm <sup>2</sup>          | WB4099 | WB4099 |
| Un-insulated, roll-crimp 0.5-6 mm <sup>2</sup>      | RB0560 | RB0560 |
| End terminals (ferrules)                            |        |        |
| 0.5-6 mm <sup>2</sup>                               | EB0560 | EB0560 |
| 4-10 mm <sup>2</sup>                                | EB4010 | EB4010 |
| 10-25 mm <sup>2</sup>                               | EB1025 | EB1025 |
| 35-50 mm <sup>2</sup>                               | EB3550 | EB3550 |

Remember to specify dies when you order a tool.