

Certified crimp tools for pre-insulated terminals 0.14 – 2.5 mm²

Technical data:

- die nests are distinctly laser marked
- adjustable if changes occur, ie after many crimps
- tested with Elpress terminals
- ratchet system which guarantees a fully closed crimp
- emergency release if the crimp sequence must be interrupted
- unique design makes the tools compact and handy
- requires minimum of muscle force for a perfect crimp
- designed to fit both right- and left-handed users
- at least 50.000 crimps
- delivered with certificate for quality assurance

DSA0115

Crimp range 0.14 – 1.5 mm²

Elpress crimp tool for symmetrical crimping of pre-insulated terminals.

Particulars:

- die nest wear inspection easily made with go/no-go gauge ESAQ 0760

Area	Cat. no.	Crimp type	Weight	Length x Width
0.14-1.5 mm ²	DSA0115	oval, symmetrical	0.445 kg	192 x 66 mm

DSA0115



Crimp type



DSA0725

Crimp range 0.5 – 2.5 mm²

Elpress crimp tool for symmetrical crimping of pre-insulated terminals.

Particulars:

- die nest wear inspection easily made with go/no-go gauge ESAQ 0760

Area	Cat. no.	Crimp type	Weight	Length x Width
0.5-2.5 mm ²	DSA0725	oval, symmetrical	0.449 kg	192 x 66 mm

DSA0725



Crimp type



ESAQ0760 – die nest gauge

ESAQ0760



Elpress go/no-go gauge for inspection of die nests in the following crimp tools: DSA0115, DSA0725, GSA0760(C) and GSEA0340C.

Particulars:

- grip Ø 8 mm
- supplied in practical plastic box
- a simple means to secure proper tool performance
- easy to use, with a GO-position and a NO GO-position for each die nest of the crimp tool.

Please contact Elpress for more information on tool calibration and QA.

Area	Cat. no.	Weight	Length
0.5-2.5 mm²	ESAQ 0760 -tolk	0.250 kg	55 mm

Tool	Checks die nest
DSA0115	■ ■ ■
DSA0725	■ ■ ■
GSA0760(C)	■ ■ ■
GSEA0340C	■ ■ ■