


Tools for Cu terminals 10 - 240 mm², Al terminals 16 - 25 mm² (-35 solid) mm² and C-sleeves 6 - 50 mm²

T2600/T2600B/T2600C

T2600/T2600B/T2600C



Mechanical handtool for crimping of Cu- and Al terminals:
 T2600 for crimping of Cu terminals type KRF/KSF 10-95 mm²
 T2600B for crimping of Cu terminals type KRD/KSD 10-120 mm²
 T2600C for crimping of Cu terminals type KRT/KST 10-120 mm²

Crimp types



| EIPRESS | | | KSF | KRF | ↓ |
|---------|------|------|-----|-----|---|
| | TB | 8 | 10 | 1 | |
| | | 9 | 16 | 1 | |
| | | 11 | 25 | 1 | |
| | | 13 | 35 | 1 | |
| | | 14,5 | 50 | 1 | |
| | | 17 | 70 | 2 | |
| | | 20 | 95 | 2 | |
| | C | | | | ↓ |
| | | C4 | 1 | | |
| | | C5 | 1 | | |
| | | C6 | 1 | | |
| | C8-9 | 2 | | | |

Information label for crimp tools T2600.

Particulars:

- rapid opening enables easy die change and quick removal after jointing
- crimp die (TB7) is available for solid 10 mm² Cu-connector, (for EXCL-type cable or similar)
- crimp force up to 57 kN
- rapid die closure and minimum handle force
- easy to operate in confined spaces
- only four dies are required to crimp 10 - 120 mm² Cu (KRD/KRT)
- rapid feed function
- supplied in a metal box
- equipped with full closure mechanism
- weight 1.9 kg
- length 440 mm, width 140 mm

V600

V600



Crimp head for crimping Cu terminals of type KRF/KSF 10–150 mm², KRD/KSD 10-185 mm², KRT/KST 10-240 mm² and C-sleeves up to 50/50 mm². Used together with footpump P4000, battery / mains powered pump P5710 and mains powered pump P1000.

Crimp types



Particulars:

- crimping force 55 kN
- robust textile bag with room for 10 die pairs
- weight 2.1 kg
- dimensions 189 x 53 x 74 mm

V611



Crimp types



V611

Hydraulic tool for crimping of Cu terminals type KRF/KSF 10-150 mm², KR D/KSD 10-185 mm², KRT/KST 10-240 mm² and C-sleeves up to 50/50 mm². Uses the same dies as T2600, V600 and PVL611.

Particulars:

- two-step, fast feed piston movement to crimp engagement which makes the crimp cycle shorter
- crimp force 60 kN
- supplied in a robust textile bag with foam rubber insert
- weight 2.5 kg
- dimensions 425 x 115 x 53 mm

PVL611

PVL611DB, supplied with 2 batteries

PVL611-US, supplied with 115 VAC charger

Battery crimp tool for crimping of Cu terminals type KRF/KSF 10-150 mm², KR D/KSD 10-185 mm² and KRT/KST 10-240 mm² and C-sleeves up to 50/50 mm². Uses the same dies as T2600, V600 and V611.

Particulars:

- flexible and ergonomic design
- buzzing signal and flashing light if right pressure is not achieved
- LED lightning for work in dark environments
- possibility to document each crimp for unique service control
- crimp force 55 kN (6 ton)
- crimps/charge: 100-200 depending on size and temperature
- crimp time: 3-6 s depending on size
- working temperature -20°C to +40°C
- environmental friendly battery, Li-Ion Makita, 1.3 Ah, 18V
- 230 VAC battery charger Li-Ion Makita, charging time 15 min
- LED indication of charge status
- for service and installation use
- supplied with robust plastic case, battery, charger and instruction manual
- weight 2.5 kg, (incl battery)
- dimensions 387 x 116 x 75 mm

PVL611



Crimp types

