

Pre-insulated TWIN end terminals 2 x 0.5 – 2 x 10mm²

Data: electrolytic copper, tin plated, CSA approved

Polypropylene insulation, colour code according to DIN 46228

Designed to connect two conductors in one terminal



	AWG	mm ²	Cat. no.	mm d	H/D	L ₁	L	s	Pcs/ pack	Rec. tool*
	2 x 20	2 x 0,5	A0,5-6ET2	1,5	2,4/4,6	6	13,0	8	100	EEB0160
			A0,5-8ET2	1,5	2,4/4,6	8	15,0	10	100	EEB0160
	2 x 20	2 x 0,75	A0,75-8ET2	1,8	2,7/5,4	8	15,0	10	100	EEB0160
			A0,75-10ET2	1,8	2,7/5,4	10	17,0	12	100	EEB0160
			A0,75-12ET2	1,8	2,7/5,4	12	19,0	14	100	EEB0160
	2 x 18	2 x 1	A1-8ET2	2,05	3,3/5,3	8	15,0	10	100	EEB0160
			A1-10ET2	2,05	3,3/5,3	10	17,0	12	100	EEB0160
			A1-12ET2	2,05	3,3/5,3	12	19,0	14	100	EEB0160
	2 x 16	2 x 1,5	A1,5-8ET2	2,3	3,5/6,5	8	16,0	10	100	EEB0160
			A1,5-12ET2	2,3	3,5/6,5	12	20,0	14	100	EEB0160
	2 x 14	2 x 2,5	A2,5-10ET2	2,9	4,1/7,7	10	18,5	12	100	EEB0160
			A2,5-13ET2	2,9	4,1/7,7	13	21,5	15	100	EEB0160
	2 x 12	2 x 4	A4-12ET2	3,8	4,9/8,7	12	23,0	14	100	GEB4010C-TWIN/ EEB0160
			A4-18ET2	3,8	4,9/8,7	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
	2 x 10	2 x 6	A6-14ET2	4,9	6,1/9,9	14	25,0	16	100	GEB4010C-TWIN/ EEB0160
			A6-18ET2	4,9	6,1/9,9	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
	2 x 8	2 x 10	A10-14ET2	6,5	7,1/12,9	14	26,0	16	100	GEB4010C-TWIN

s = strip length

* Use die nest marked closest to the total cross section area in the terminal