

Pre-insulated end terminals for short-circuit proof cable-insulations 1.5 – 16mm²

Data: Cu 99.95%, tin plated, colour code DIN

Insulation polypropylene



| | mm ² | Cat. no. | mm d | L ₁ | L | S | Rec. tool | Pcs/pack |
|---|-----------------|--------------|------|----------------|------|----|-----------|----------|
| ■ | 1,5 | A1,5-8ETDXL | 6,9 | 8 | 17,5 | 11 | EEB0160 | 100 |
| | | A1,5-10ETDXL | 6,9 | 10 | 19,5 | 13 | EEB0160 | 100 |
| ■ | 2,5 | A2,5-8ETDXL | 7,8 | 8 | 17,5 | 11 | EEB0160 | 100 |
| | | A2,5-12ETDXL | 7,8 | 12 | 21,5 | 15 | EEB0160 | 100 |
| ■ | 4 | A4-10ETDXL | 7,8 | 10 | 19,5 | 13 | EEB0160 | 100 |
| ■ | 6 | A6-12ETDXL | 8,3 | 12 | 23 | 15 | EEB0160 | 100 |
| ■ | 10 | A10-12ETDXL | 9,8 | 12 | 24 | 15 | GEB1025 | 100 |
| ■ | 16 | A16-12ETDXL | 12 | 12 | 25,5 | 15 | GEB1025 | 100 |

s = stripping length