

## Through connectors, 10 - 800 mm<sup>2</sup> KST


**Data:** electrolytic copper, tin-plated.

Cable inspection hole and cable stop, for stranded (class 2) Cu-conductors

UL-approved (10-500 mm<sup>2</sup>), DNV-approved (10-400 mm<sup>2</sup>)

**Marking example: 18 95 Elpress logotype included**

18 = die no. 95 = mm<sup>2</sup>



| AWG  | Cat. no. | mm d | D   | L   | Pcs/Pack | Die no. | Rec. tool   |
|------|----------|------|-----|-----|----------|---------|-------------|
| 8    | KST10    | 4,5  | 7   | 30  | 100      | 7       | GWB4099     |
| 6    | KST16    | 5,5  | 8,5 | 35  | 100      | 8,5     | V600, V1300 |
| 4    | KST25    | 7    | 10  | 40  | 100      | 10      | V600, V1300 |
| 2    | KST35    | 8,5  | 12  | 45  | 100      | 12      | V600, V1300 |
| 1/0  | KST50    | 10   | 14  | 50  | 50       | 14      | V600, V1300 |
| 2/0  | KST70    | 12   | 16  | 55  | 50       | 16      | V600, V1300 |
| 4/0  | KST95    | 13,5 | 18  | 60  | 50       | 18      | V600, V1300 |
| 250  | KST120   | 15   | 19  | 60  | 50       | 19      | V1300, V250 |
| 300  | KST150   | 17   | 22  | 65  | 50       | 22      | V1300, V250 |
| 350  | KST185   | 19   | 24  | 75  | 50       | 24      | V1300, V250 |
| 500  | KST240   | 21   | 26  | 85  | 50       | 26      | V1300, V250 |
| 600  | KST300   | 24   | 30  | 90  | 50       | 30      | V1300, V250 |
| 750  | KST400   | 26   | 32  | 90  | 50       | 32      | V1300, V250 |
| 1000 | KST500   | 31   | 40  | 135 | 5        | 40      | V250        |
|      | KST630   | 34   | 45  | 135 | 5        | 45      | V250        |
|      | KST800   | 39   | 53  | 175 | 1        | 53      | V250        |