

Tube terminals, KRF, 16 - 800 mm²


Data: electrolytic copper, tin-plated.

Cable inspection hole, for flexible (class 5) and stranded (class 2) Cu-conductors.

UL-approved (16-500 mm²), DNV-approved (16-400 mm²).

Marking example KRF: 95 12F, KR D: 500 16 (Elpress logotype included)

95 = mm² 12 = palm hole for M12 F = type KRF, for stranded and flexible conductors
 500 = mm² 16 = palm hole for M16



AWG	Cat. no. mm ² - bolt hole M	mm W	d	N	N ₁	L	Pcs/ pack	Die no.	Rec. tool
6	KRF16-6	13,0	6,0	8,0	9,0	34	100	9	V600, V1300
6	KRF16-8	13,0	6,0	8,0	9,0	34	100	9	V600, V1300
6	KRF16-10	16,0	6,0	10,0	11,0	38	100	9	V600, V1300
6	KRF16-12	22	6,0	12,0	13,0	47	100	9	V600, V1300
4	KRF25-6	16,0	8,0	8,0	10,0	39	100	11	V600, V1300
4	KRF25-8	16,0	8,0	8,0	10,0	39	100	11	V600, V1300
4	KRF25-10	17,0	8,0	10,0	11,0	42	100	11	V600, V1300
4	KRF25-12	22	8,0	12,0	13,0	47	100	11	V600, V1300
2	KRF35-6	18,0	9,0	10,0	11,0	47	100	13	V600, V1300
2	KRF35-8	18,0	9,0	10,0	11,0	47	100	13	V600, V1300
2	KRF35-10	18,0	9,0	10,0	11,0	47	100	13	V600, V1300
2	KRF35-12	22	9,0	12,0	14,0	52	100	13	V600, V1300
1/0	KRF50-6	21	11,0	11,0	12,0	50	100	14,5	V600, V1300
1/0	KRF50-8	21	11,0	11,0	12,0	50	100	14,5	V600, V1300
1/0	KRF50-10	21	11,0	11,0	12,0	50	100	14,5	V600, V1300
1/0	KRF50-12	21	11,0	12,0	14,0	53	100	14,5	V600, V1300
1/0	KRF50-16	27	11,0	15,0	17,0	59	100	14,5	V600, V1300
2/0	KRF70-6	25	13,0	11,0	12,0	55	50	17	V600, V1300
2/0	KRF70-8	25	13,0	11,0	12,0	55	50	17	V600, V1300
2/0	KRF70-10	25	13,0	11,0	12,0	55	50	17	V600, V1300
2/0	KRF70-12	25	13,0	12,0	14,0	58	50	17	V600, V1300
2/0	KRF70-16	28	13,0	15,0	17,0	64	50	17	V600, V1300
4/0	KRF95-8	29	15,0	15,0	17,0	69	50	20	V600, V1300
4/0	KRF95-10	29	15,0	15,0	17,0	69	50	20	V600, V1300
4/0	KRF95-12	29	15,0	15,0	17,0	69	50	20	V600, V1300
4/0	KRF95-16	29	15,0	15,0	17,0	69	50	20	V600, V1300
250	KRF120-10	32	17,0	15,0	17,0	73	25	22	V1300, V250
250	KRF120-12	32	17,0	15,0	17,0	73	25	22	V1300, V250
250	KRF120-16	32	17,0	15,0	17,0	73	25	22	V1300, V250
300	KRF150-10	36	19,0	15,0	16,0	80	25	25	V1300, V250
300	KRF150-12	36	19,0	15,0	16,0	80	25	25	V1300, V250
300	KRF150-16	36	19,0	15,0	16,0	80	25	25	V1300, V250
300	KRF150-20	36	19,0	19,0	19,0	87	25	25	V1300, V250
350	KRF185-10	39	21	15,0	16,0	86	20	27	V1300, V250
350	KRF185-12	39	21	15,0	16,0	86	20	27	V1300, V250
350	KRF185-16	39	21	15,0	16,0	86	20	27	V1300, V250
350	KRF185-20	39	21	19,0	19	93	20	27	V1300, V250
500	KRF240A-10	42	22,5	19	20	96	10	30	V1300, V250
500	KRF240A-12	42	22,5	19	20	96	10	30	V1300, V250
500	KRF240A-16	42	22,5	19	20	96	10	30	V1300, V250
500	KRF240A-20	42	22,5	19	20	96	10	30	V1300, V250

** total palm length

AWG	Cat. no. mm ² - bolt hole M	mm W	d	N	N ₁	L	Pcs/ pack	Die no.	Rec. tool
600	KRF300A-10	46	24,5	15	19	93	10	32	V1300, V250
600	KRF300A-12	46	24,5	15	19	93	10	32	V1300, V250
600	KRF300A-16	46	24,5	20	20	99	10	32	V1300, V250
600	KRF300A-20	46	24,5	23	25	99	10	32	V1300, V250
600	KRF300A-24	46	24,5	23	25	107	10	32	V1300, V250
750	KRF400A-00	56	30	-	-	118	10	38	V1300, V250
750	KRF400A-12	56	30	15	25	111	10	38	V1300, V250
750	KRF400A-16	56	30	20	20	111	10	38	V1300, V250
750	KRF400A-20	56	30	23	25	118	10	38	V1300, V250
750	KRF400A-24	56	30	23	25	118	10	38	V1300, V250
For flexible Cu-conductors									
1000	KRF500-00	61	33	70**		160	5	42	V250
1000	KRF500-16	61	33	25	35	150	5	42	V250
1000	KRF500-20	61	33	25	35	150	5	42	V250
1000	KRF500-24	61	33	25	35	150	5	42	V250
	KRF630-00	75	39	80**		195	1	53	V250
	KRF630-20	75	39	35	45	195	1	53	V250
	KRF630-24	75	39	35	45	195	1	53	V250
	KRF800-00	75	42	80**		195	1	53	V250
	KRF800-24	75	42	35	45	195	1	53	V250