

Tube terminals 45°, KRF, 10 - 150 mm²


Data: electrolytic copper, tin-plated.

Cable inspection hole, for stranded (class 2) and flexible (class 5) Cu-conductors.

UL-approved (35-150 mm²), DNV-approved (16-150 mm²).

Marking example KRF: 70 10F (Elpress logotype included)

70 = mm² 10 = palm hole for M10 F = type KRF, for stranded and flexible conductors



AWG	Cat. no. mm ² , Bolt, 45°	mm W	d	N	N ₁	A	Pcs/ pack	Die no.	Rec. tool
8	KR10-6-45GR	13,0	5,0	6,5	11,5	19	100	8	V600, V1300
8	KR10-8-45GR	13,5	5,0	8,5	12,0	19	100	8	V600, V1300
6	KRF16-6-45GR	13,0	6,0	6,5	11,5	23	100	9	V600, V1300
6	KRF16-8-45GR	13,5	6,0	8,5	12,0	23	100	9	V600, V1300
4	KRF25-6-45GR	16,0	8,0	6,5	11,5	24	100	11	V600, V1300
4	KRF25-8-45GR	16,0	8,0	8,5	12,0	24	100	11	V600, V1300
4	KRF25-10-45GR	17,0	8,0	11,5	13,5	24	100	11	V600, V1300
2	KRF35-6-45GR	18,0	9,0	6,5	11,5	30	100	13	V600, V1300
2	KRF35-8-45GR	18,0	9,0	8,5	12,0	30	100	13	V600, V1300
2	KRF35-10-45GR	18,0	9,0	11,5	13,5	30	100	13	V600, V1300
1/0	KRF50-8-45GR	21	11,0	8,5	17,5	31	100	14,5	V600, V1300
1/0	KRF50-10-45GR	21	11,0	11,5	18,5	31	100	14,5	V600, V1300
1/0	KRF50-12-45GR	21	11,0	12,5	19,5	31	100	14,5	V600, V1300
2/0	KRF70-8-45GR	25	13,0	8,5	17,5	35	50	17	V600, V1300
2/0	KRF70-10-45GR	25	13,0	11,5	18,5	35	50	17	V600, V1300
2/0	KRF70-12-45GR	25	13,0	12,5	19,5	35	50	17	V600, V1300
4/0	KRF95-10-45GR	29	15,0	11,5	18,5	40	50	20	V600, V1300
4/0	KRF95-12-45GR	29	15,0	12,5	19,5	40	50	20	V600, V1300
4/0	KRF95-16-45GR	29	15,0	15,5	20,5	40	50	20	V600, V1300
250	KRF120-10-45GR	32	17,0	11,5	18,5	43	25	22	V1300, V250
250	KRF120-12-45GR	32	17,0	12,5	19,5	43	25	22	V1300, V250
250	KRF120-16-45GR	32	17,0	15,5	20,4	43	25	22	V1300, V250
300	KRF150-10-45GR	36	19,0	11,5	18,5	49	25	25	V1300, V250
300	KRF150-12-45GR	36	19,0	12,5	19,5	49	25	25	V1300, V250
300	KRF150-16-45GR	36	19,0	15,5	20,5	49	25	25	V1300, V250