## **Raytronics** AG

Wärmeschrumpftechnik

## Tabs different styles

Data: brass, tin-plated

1	12 00-
2	N
3	e- LW-
4	2
5	et 012

	Cat. no.	mm W	e	L.		Pcs/ pack
1	B07FLS1H	8,5	8,0	8,5	6,3x0,8	100
2	B07FLS2H	9,0	7,5	18,5	6,3x0,8	100
3	B07FLS3H	8,0	7,5	21	6,3x0,8	100

Fig	Cat. no.	mm W	L	Tabs	Pcs/ pack
4	B07FLS	7,5	9,0	6,3x0,8	100

Fig	Cat. no.	mm W	e	ø	L	Tabs	Pcs/ pack
5	B1807H4	8,1	8,3	4,4	19,1	6,3x0,8	100
5	B1807H5	8,0	8,3	5,4	19,2	6,3x0,8	100

Fig	Cat. no.	mm b	e	ø	c	Tabs	Pcs/ pack	Angle
6	B0457H4	8,0	8,0	4,1	8,0	6,3x0,8	100	45°
6	B0457H5	8,0	8,0	5,3	8,0	6,3x0,8	100	45°
7	B0907H4	8,0	8,3	4,1	8,0	6,3x0,8	100	90°
7	B0907H5	8,0	8,0	5,3	8,0	6,3x0,8	100	90°

Fig	Cat. no.	mm W	c	e	ø	L	Tabs	Pcs/ pack	
8	B2457H4	10,0	12,0	8,0	4,2	10,0	6,3x0,8	100	2x45°
8	B2457H5	10,0	12,0	8,0	5,2	10,0	6,3x0,8	100	2x45°
Ø hole	diameter.								

	~~~
6	010
7	Le.
8	Pe.
12	C mile